REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2011-04-21







P.C.B LAYOUT

Technical Data

Material:
Contact Material: Brass
Contact plating:Au or Sn Over 50μ" Ni
Insulator Material:Black Polyester UL94V-0
Standard:PBT/PA6T+30%G.F

Electrical:
Current rating:2.0Amps/contact max.
Contact resistance: ≤20mΩ/contact
Insulation resistance: ⩾1000MΩ at V=100V
Withstanding Voltage:1000V AC/minute

Mechanical:
Mechanical life cycle:min.200
Operaing temperature: -40°C to +105°C
Soldering temperature: +255°C

包装方式：袋装

Dimension antitheses list (尺寸选型表)					
Item (项目)	L	PA	PC	H1	H2
Standard (尺寸)					
Remarks (备注)	以上尺寸可由客户选择				

PZ	2	XX	21	XXX	D	XX	X	N	N	XXX
品名 PZ=排针	间距 2=2.00	塑高 10=1.00mm 15=1.50mm 20=2.00mm	产品类型 21=双塑单排	PIN位总数 01~40P	产品折弯类型 D=直插	表面处理 SN=Tin120u" MT=镀雾锡 GF=Gold Flash G1=Gold 1u" G2=Gold 2u" G3=Gold 3u" G4=Gold 5u" G5=Gold 8u" G6=Gold 10u" G7=Gold 15u" G8=Gold 30u" GA=Gold1.5u" S0=半金锡	塑胶材质 A=PBT B=PA46 C=PA6T D=PA66 E=PA9T F=LCP	塑胶特性 N=常规	排针盖 N=无	针长 针长=PA+PC+PD

NICETYCONN® 深圳市创辉诚科技有限公司
SHENZHEN CHUANGHUICHENG TECHNOLOGY CO.,LTD

TOLERANCE		PROJECTON		TITLE: 单排双塑180度排针 PH2.00 系列图			
ANGLE	±5°	DATE :	2011-04-21				
X.XXX	±0.10	DRAWN :		PART NO: PZ2XX21XXXDXXXNNXXX			
X.XX	±0.20	CHECKED :		DRAWING NO: PZ2XX21DXXX034			
X.X	±0.30	APPROVED :		REV: A0	UNIT: mm	SCALE: 4:1	SIZE: A4
X.	±0.50						